PATENTED

Forgot to lubricate? Never again!

LUBRITOOL®

REUSABLE
Replaceable grease cartridge

EXTREMELY DURABLE
Robust cartridge housing

UNIVERSAL APPLICATION
HSK and CAPTO™ interfaces

FITS INTO ANY TOOL MAGAZINE
The same size as an end mill

360°-LUBRICATION
Patented distribution ring

MADE IN GERMANY

Fully Automated Lubrication of Clamping Sets. LUBRITOOL®.

Lubricating tool clamping systems is still often performed manually, even on automated milling machines and machining centers. Lubrication is required after 75 operating hours or 20,000 tool changes. Failure to lubricate on time can lead to wear and machine downtime. LUBRITOOL® is the world's first tool for the automated lubrication of tool clamping systems. It is a patented solution from RÖHM, the clamping and gripping technology specialist with more than 100 years of experience. Like a cutting tool, LUBRITOOL® remains in the tool magazine until lubrication is required. When the machine control signals a lubrication cycle, it is automatically loaded into the spindle. During clamping and unclamping, its pressure element generates lubrication pulses, while the distribution ring ensures complete 360° grease distribution. LUBRITOOL® is approved for RÖHM HSK and OTT-JAKOB CAPTO™ clamping units.

FIVE GOOD REASONS FOR LUBRITOOL®

1 REDUCE MAINTENANCE TIME
From 5 minutes down to just 5 seconds per lubrication cycle

2 LUBRICATE PROFESSIONALLY
Prevent clamping set wear

3 LUBRICATE AT THE RIGHT TIME
No more clamping set wear

4 SAVE RESOURCES
Always optimal lubricant dosage

5 NO MANUAL EFFORT REQUIRED
Fully automatic loading via tool magazine

The patented distribution ring of Lubritool® ensures ideal lubricant distribution inside the clamping sets.

	ID 1334394	ID 1334306	ID 1330233	ID 1323415	ID 1323477
Interface design (IS012164-1) HSK A/C/E/T	40	50	63	100	-
Interface design (IS012164-1) HSK B/D/F	50	63	80	125	-
Interface design CAPTO™	-	-	-	-	C6
Tool interface length (mm)	45	46,1	48	50,5	27
Overall length with grease cartridge* (mm)	188,6	189,6	191,5	194	208,5
Diameter (mm)	65	65	65	65	65
Weight without grease cartridge* (kg)	1,0	1,1	1,4	2,7	1,5
Weight with grease cartridge* (kg)	1,2	1,3	1,6	2,9	1,7
Number of lubrication cycles per grease cartridge*	100	100	100	50	100

* Lubriflux by RÖHM **(ID 1339629)**

USA
Roehm Products of America Inc.
2500 Northlake Drive
Suwanee GA 30024
TEL +01 770 963 8440
FAX +01 770 963 8407
sales@rohm-products.com
www.rohm-products.com

UK
ROHM (Great Britain) LTD.
27 Webb Ellis Business Park,
Woodside Park,
Rugby, CV21 2NP
TEL +44 17 88 22 84 69
roehmgb@roehm.biz
www.roehm.biz/en

GERMANY
RÖHM GmbH
Heinrich-Roehm-Straße 50
89567 Sontheim/Brenz
Germany
TEL +49 7325 16 400
sales@roehm.biz
service@roehm.biz

roehm.biz

Subject to change. ID No. 1423759 / 0926